



Tel: 01832 732216

E-mail: [info@upholsteryleather.co.uk](mailto:info@upholsteryleather.co.uk)

Web: [www.upholsteryleather.co.uk](http://www.upholsteryleather.co.uk)

## RANGE: DELTA

Delta is a beautifully soft, supple & pigmented corrected grain hide with a small, uniform emboss to help maximise the cutting yield and durability.

### LEATHER INFORMATION

Durability: High Resistance

Grain: Small embossed corrected grain

Hide Origin: New Zealand, USA, Australia

Average Size: 50sq.ft (4.65sq.m)

Thickness:0.9/1.1mm

Leather Type: Pigmented

TEST SPECIFICATION	VALUE
Light resistance (Xenon test) I.U.F. 402 - UNI EN ISO 105-B02	5 blue scale
Colour fastness to dry rubbing I.U.F. 450 - UNI EN ISO 11640	≥ 4 500 cycles grey scale
Colour fastness to wet rubbing I.U.F. 450 - UNI EN ISO 11640	≥ 4 150 Cycles grey scale
Colour fastness to Alkaline pH8 I.U.F. 450 - UNI EN ISO 11640	≥ 4 80 Cycles grey scale
Adhesion I.U.F. 470 UNI EN ISO 11644	≥3.5 N/cm
Flexing Endurance I.U.P. 20 UNI EN ISO 5402	>30,000
Tear Strength I.U.P 40 - UNI EN ISO 3377-1	≥ 20 N
Flammability BS 5852 part 1 - UK Cigarette & Match of the Furnishings (Fire) (Safety)Regulations 1988	Pass

### Care information:

- Avoid exposing to direct sunlight or direct heat.
- Avoid sharp objects such as studs, buckles & zips coming into contact with the Leather.
- Dust and vacuum your leather regularly
- Wipe off stains and spills immediately with a soft, light damp cloth taking care not to soak the leather
- These Hides do not need to be fed and the use of saddle soap or wax polishes should be avoided, especially spray polishes.
- Use of general household cleaning products, chemicals and abrasives are not recommended as they can breakdown the protective surface and cause damage.
- Do not use any method or product not recommended by the manufacturer.

This specification sheet replaces any copies in your possession. The values indicated in this sheet refer to the leather at the time of supply. Once the leather has been processed, cut or marked we can no longer guarantee the same values. V.100117